



the andersen company

A HISTORY OF BEING AHEAD OF OUR TIME

## PRODUCT DESCRIPTION: COMFORT FLOW Product # 420

### GENERAL SPECIFICATIONS:

<b>SURFACE:</b>	<b>Type:</b>	Nitrile Rubber High Density Closed Cell Foam
<b>BACKING:</b>	<b>Type:</b>	Nitrile Rubber High Density Closed Cell Foam
	<b>Thickness:</b>	3/8"
	<b>Color:</b>	Black
	<b>Durometer:</b>	50 to 55 Shore A

### FEATURES:

- Treated with an anti-microbial agent
- Provides superior anti-fatigue properties for employee comfort and ergonomic benefits.
- Constructed of 100% high density, closed-cell Nitrile rubber cushion for maximum resistance to water, oils, greases, chemicals, and animal fats.
- Lightweight, outperforms most thicker, heavier mats and is easy to clean by pressure washing or hosing off.
- Beveled edges around the mat help to minimize trip and fall accidents.
- Slip resistant surface helps to reduce slip and fall accidents. Liquids and debris flow easily through the holes and away from shoes.
- ASTM C1028-96 Static Coefficient of Friction: Dry - .70 Wet - .69
- Anti-static: Electrical Resistance - IBM (Surface to Ground) ASTM F-150 & NFPA 99 Chapter 12 Section 4.1.3.8 (6) (7), 1990. Average Electrical Resistance at 70° F. and 50% Relative Humidity:  $5.4 \times 10^8$  ohms.
- Passes Flammability Standard DOC-FF-1-70
- Passes AATCC Test Method 134-1991 Electrostatic Propensity of Carpets. Maximum Voltage Negative 0.3 KV.
- U.V. Stable