

Gym Floor Mats

#1 selling rubber Gym Tiles

The General Mat Company recommends a thorough cleaning and maintenance program for Gym Floor Mats.

Maintenance Guide

Post installation protection and maintenance of Gym Floor Mats should be specified by the designer/architect. Gym Floor Mats in most cases do not come pre-finished, therefore the flooring after installation should not be subjected to dirt, dust, debris and potential damage from the surrounding construction activities.

The General Mat Company recommends that the specifier should determine which party will be responsible for the initial cleaning and application of the Protect-A-Gloss finish to the floor. To perform the initial cleaning, brush the surface with a stiff bristle broom and then vacuum and dust mop until it is totally clean. Allow to dry thoroughly.

It is required that all Gym Floor Mat floors be coated with two coats of Protect-A-Gloss floor finish which should be applied with a 10mm nap roller prior to use. Provide sufficient curing time between coats as well as after the final coat before allowing foot traffic (this should be at least 24 hours).

It is recommended that daily/regular cleaning should be performed by sweeping, dust mopping or vacuuming or remove all dust, dirt and debris. For heavy cleaning use a solventless heavy cleaning agent.

It is recommended that Gym Floor Mats flooring from time to time, when the look calls for it, be re-finished with Protect-A-Gloss floor finish following the standard Protect-A-Gloss application procedures.

Phone: 02 9682 1999 Fax: 02 9682 1988
Unit 5, 40 George Street, Granville, NSW 2142
PO Box 7088, Silverwater, NSW 1811
Website: www.matting.com.au
Email: sales@matting.com.au

