



A HISTORY OF BEING AHEAD OF OUR TIME

PRODUCT DESCRIPTION: WATERHOG FASHION Product # 280

GENERAL SPECIFICATIONS:

SURFACE:	Fiber Type:	Needlepunched Solution-dyed polypropylene, outstanding light fastness
	Weight:	24 ozs./sy.
	Nub Height:	1/4"
	Design:	Square "waffle"
BACKING:	Type:	100% SBR Rubber (15% Recycled content)
	Thickness:	.110" - Border .190" - Nubs .050" - Between Nubs
	Durometer:	60
	Tensil:	1100

FEATURES:

- Reinforced face NUBS: Face NUBS are reinforced with rubber to resist crushing, maintaining high performance and extending product life.
- "Water Dam" FABRIC border: Border is designed to hold water and dirt on mat keeping them off carpets and floors. Unique raised fabric border allows Fashion mats to hold up to 1 1/2 gallons of water per square yard. Some styles available without dam for outside use, so water can drain easily.
- Raised NUB surface: Removes and traps dirt and moisture and holds it on mat below shoe level so it is not tracked in.
- TriGrip backing: Gripping action minimizes movement on most carpets and improves traction on hard surfaces.
- Rubber backing: Lays flat, won't crack or curl like vinyl mats.
- Indoor/Outdoor: Durable polypropylene face suitable for indoor or outdoor use. Polypropylene fiber system dries quickly preventing fading and rotting.
- Easy to clean: Just vacuum or hose off and hang to dry.
- Colorfast: Solution dyed for excellent light and wet fastness.
- Not adversely effected by salt or ice melt.
- Should not be used in areas exposed to animal fats (kitchens) or petroleum products.
- Passes Flammability Standard DOC-FF-1-70
- Anti-static rating averaging 1.2 KV with a maximum average voltage of 1.63 KV as measured by the AATCC 134 Electrostatic Propensity Test and meets IBM's minimum standard for electrical resistance (NFPA99). Waterhog mats are safe for use in computer rooms and around electronic equipment.
- ASTM C 1028-29 Static Coefficient of Friction. Dry .70